



DISTRIBUTOR  
 Bowman Construction Supply  
 10801 E. 54th Avenue  
 Denver, CO 80239  
 Phone: (303) 696-8960  
[www.bowmanconstructionsupply.com](http://www.bowmanconstructionsupply.com)

**Reinforced (Wireback) Silt Fence**

This product is manufactured by applying 3 feet of silt fence fabric to a 2 ft. roll of 14awg Wire Mesh. The material overlaps the top of the wire by 3 inches making the bottom flap at 9 inches. The material is secured to the top of the wire mesh with hog rings every 12 inches.

**Application: Sediment Control**

PROPERTY	TEST METHOD	UNIT	ROLL VALUE
Grab Tensile	ASTM D 4632	Lbs	135
Grab Elongation	ASTM D 4632	%	16% x 20%
Mullen Burst	ASTM D 3786	PSI	300 Psi
Puncture	ASTM D 4833	Lbs	50 Lb
Trapezoidal Tear	ASTM D 4533	Lbs	70
AOS	ASTM D 4751	Sieve	30 U.S. Sieve
Flow Rate	ASTM D 4491	Gpm/ft	14
Permittivity	ASTM D 4491	Sec-1	0.1 Sec-1
UV Resistance	ASTM D 4355	% hours	80%@500hrs

**14 awg Wire Mesh - 2' x 100' roll of Galvanized Steel Welded Wire 14 awg. Aperture opening of the mesh is 2" x 4".**

**Weight: Each prefabricated roll weighs approximately 35 lbs.**

**Shipping: Skids of 25 rolls can be provided.**

