



DeWitt Company Key Landscape Fabric & Groundcover Specifications

DEWITT LANDSCAPE FABRIC & WOVEN GROUNDCOVER	ASTM	MECHANICAL PROPERTIES					ENDURANCE PROPERTIES	HYDRAULIC PROPERTIES			PHYSICAL PROPERTIES		
		Grab Tensile Strength (LBS)	Elongation %	Trapezoid Tear LBS	Puncture LBS	CBR Puncture LBS	Mullen Burst PSI	UV Stability % @ 500hrs	Permittivity sec-1	Water Flow Rate gpm/sqft / I/min/sqmt	Apparent Opening size US Sieve# (mm)	Weight oz/sqyd	thickness MILS
Pro5 Weed Barrier	ASTM	Warp - 100 Weft - 100 D-4632	Warp - 15 Weft - 15 D-4632	Warp - 40 Weft - 26 D-4533	65 D-4833	 D-3786	230 D-4355	>70% after 2500 Hrs	12 D-4491		5 D-3776	32 D-1777	
20 YEAR WEED BARRIER	ASTM	Warp - 95 Weft - 50 D-4632	Warp - 12 Weft - 12 D-4632	Warp - 35 Weft - 20 D-4533	55 D-4833	 D-3786	240 D-4355	>70% after 2500 hrs	15 D-4491		4.1 D-3776	24 D-1777	
SUNBELT WOVEN GROUNDCOVER	ASTM	Warp - 175 Weft - 110 D-4632	Warp - 25 Weft - 25 D-4632	Warp - 80 Weft - 60 D-4533	50 D-4833	 D-3786	310 D-4355	>70% after 2500 hrs	12 (10'-15.5') 2.5 (3'-6')		3.2 D-3776	21 D-1777	
WEED BARRIER PRO BLACK	ASTM	MD - 55 CD - 50 D-5034	MD - 40 CD - 80 D-5034	MD - 25 D-4533	 	 D-3786	75 D-4355		0.5 D-4491	40 D-4491	3 D-3776	24.4 D-1777	
CONTRACTOR'S SELECT BLACK & GREY / TYPAR PREMIUM 3201	ASTM	73 D-4632	>70 D-4632	25 D-4533	23 D-4833				3 D-4491	200 D-4491	0.52 D-3776	1.9 D-1777	11.5
CONTRACTOR'S SELECT PLUS BLACK / TYPAR PROFESSIONAL 3301	ASTM	120 D-4632	>70 D-4632	46 D-4533	32 D-4833				1.2 D-4491	70 D-4491	0.24 D-3776	3 D-1777	15
CONTRACTOR'S SELECT PLUS GREY	ASTM	MD - 106 XD - 103 D-4632	 	MD - 53 XD - 47 D-4533	 						2.5 D-5261	13.4 D-1777	
12 YEAR WEED BARRIER	ASTM	MD - 55 CD - 50 D-5034	MD - 40 CD - 80 D-5034	MD - 25 D-4533	 	 D-3786	75 D-4355		0.5 D-4491	40 D-4491	3 D-3776	24.4 D-1777	
6 YEAR WEED BARRIER	ASTM	MD - 18 CD - 15 D-5034	MD - 100 CD - 200 D-5034	 	 				1.5 D-4491	110 D-4491	1.5 D-3776	18 D-1777	
3 YEAR WEED BARRIER	ASTM	MD - 14 CD - 12 D-3776	MD - 125 CD - 250 D-5034	 	 				1.5 D-4991	110 D-4991	1 D-3776	16 D-1777	